

## BHLX3-00-160X320-X-R-24V

## CABLE & CONNECTOR EMITTING AREA A X Ø 3.20 THRU



| Mechanical Information    |                              |
|---------------------------|------------------------------|
| Casing Material           | Aluminium                    |
| Storage Temperature Range | Temp 0-45°C, Humidity 20-85% |
| Weight                    | 1062 g                       |
| Length / Outer Diameter   | 356 mm                       |
| Width / Inner Diameter    | 178 mm                       |
| Thickness / Height        | 30 mm                        |



## BHLX3-00-160X320-X-R-24V

| Optical Information                |                                                      |                                                                   |                                                |             |  |  |  |
|------------------------------------|------------------------------------------------------|-------------------------------------------------------------------|------------------------------------------------|-------------|--|--|--|
| Part Number                        |                                                      |                                                                   | BHLX3-00-160X320-X-R-24V                       |             |  |  |  |
| LED Color                          |                                                      |                                                                   | RED                                            |             |  |  |  |
| Wavelength                         | (nm)                                                 |                                                                   | 630                                            |             |  |  |  |
| Intensity (±15%)                   | (Lux)                                                | TBA                                                               | TBA                                            | TBA         |  |  |  |
| Working Distance                   | (mm)                                                 | 10                                                                | 20                                             | 30          |  |  |  |
| Illumination (number of row)       | (                                                    |                                                                   | Х                                              |             |  |  |  |
| Illumination Active Area           | t                                                    |                                                                   |                                                |             |  |  |  |
| Active Length / Outer Diameter     | (mm)                                                 | 320                                                               |                                                |             |  |  |  |
| Active Width / Inner Diameter      | (mm)                                                 |                                                                   |                                                |             |  |  |  |
| Emission angle                     | (deg.)                                               | 160                                                               |                                                |             |  |  |  |
| Eye Safety Class ( IEC62471 )      | (ueg.)                                               | 0<br>EXEMPT                                                       |                                                |             |  |  |  |
| Lye Janety Class ( ILCO247 I )     |                                                      |                                                                   | LALIWIFT                                       |             |  |  |  |
| Electrical Information             |                                                      |                                                                   |                                                |             |  |  |  |
| Lighting Supply Voltage            |                                                      |                                                                   |                                                |             |  |  |  |
| (constant voltage mode)            |                                                      | 24V ± 2%                                                          |                                                |             |  |  |  |
| Continuous Current                 | (mA)                                                 |                                                                   |                                                |             |  |  |  |
| Power Consumption                  | (MA)<br>(W)                                          | 1080<br>25.92                                                     |                                                |             |  |  |  |
| Lighting casing temperature,       | (**)                                                 | 25.92                                                             |                                                |             |  |  |  |
| Operating after 60 minutes         | °C                                                   | TBA                                                               |                                                |             |  |  |  |
| Operating after 60 minutes         | L L                                                  |                                                                   | TBA                                            |             |  |  |  |
| Strobe Mode Specification          |                                                      |                                                                   |                                                |             |  |  |  |
| Pulse Operation                    | I                                                    |                                                                   | YES                                            |             |  |  |  |
| Max. Lighting Supply Voltage       |                                                      | Pulsing at 24VDC to 48VDC, 0-10% Duty Cycle                       |                                                |             |  |  |  |
| (Constant voltage power supply)    | (V)                                                  | Pulsing at 24VDC to 48VDC, U-10% Duty Cycle  Recommended at 36VDC |                                                |             |  |  |  |
|                                    |                                                      |                                                                   | Recommended at 36VDC                           |             |  |  |  |
| Pulse Current, (Max. 10msec)       | (mA)                                                 | 3240                                                              |                                                |             |  |  |  |
| (Constant current power supply)    |                                                      |                                                                   |                                                |             |  |  |  |
| Max. Trigger Pulse Duration        | (msec)                                               |                                                                   |                                                |             |  |  |  |
| Duty Cycle                         | 0-10%                                                |                                                                   |                                                |             |  |  |  |
|                                    |                                                      |                                                                   |                                                |             |  |  |  |
| Additional Information             |                                                      |                                                                   |                                                |             |  |  |  |
| Additional Cooling Method          | Attached to machine part for better heat dissipation |                                                                   |                                                |             |  |  |  |
| Intensity Controller Selection     | ANG, ST, SD and SDA Series                           |                                                                   |                                                |             |  |  |  |
| CE Conformity                      | YES                                                  |                                                                   |                                                |             |  |  |  |
| RoHS Compliance                    | YES                                                  |                                                                   |                                                |             |  |  |  |
|                                    |                                                      |                                                                   |                                                |             |  |  |  |
| Connection                         |                                                      |                                                                   |                                                |             |  |  |  |
| Connector Type (Default):          |                                                      | JST SMR-03V                                                       |                                                |             |  |  |  |
| Cable Length out from lighting :   | (mm)                                                 | 500                                                               |                                                |             |  |  |  |
| Pin Configuration :                | ,,                                                   | Pin                                                               | Signal                                         | Cable Color |  |  |  |
| co.niguration .                    | <del>                                     </del>     | 1                                                                 | LED +                                          | RED         |  |  |  |
|                                    | <del>                                     </del>     | 2                                                                 | N.C.                                           |             |  |  |  |
|                                    | <del>                                     </del>     |                                                                   |                                                |             |  |  |  |
|                                    | <del>                                     </del>     | 3                                                                 | LED -                                          | WHITE       |  |  |  |
|                                    |                                                      |                                                                   |                                                |             |  |  |  |
|                                    |                                                      |                                                                   |                                                |             |  |  |  |
| Application                        |                                                      |                                                                   |                                                |             |  |  |  |
|                                    | Backlight Illumination                               |                                                                   |                                                |             |  |  |  |
| Illumination Type                  |                                                      |                                                                   |                                                |             |  |  |  |
| Illumination Type Applicattion Use |                                                      | Lead frame i                                                      | nspection, shape recognition, size measurement |             |  |  |  |



Thank you for downloading this document from www.machine-vision-shop.com

If you have any questions, you need help composing the right package for your application or do you want to order?

Feel free to contact us via e-mail at sales@vision-consultancy.nl or visit our webshop.

Our vision experts are happy to help you.



Natascha Overhof



Christian Crompvoets



## **VISION** CONSULTANCY

Robert Schumandomein 2 6229 ES Maastricht The Netherlands

+31 (0) 438 522 651

sales@vision-consultancy.nl www.machine-vision-shop.com

