


ILLUMINATOR DATA-ID

BHP1010-X-R-24V

Lighting Dimension





Mechanical Information	
Casing Material	Aluminium
Storage Temperature Range	Temp 0 - 45°C, Humidity 20-85%
Weight	650 g
Length / Outer Diameter	132 mm
Width / Inner Diameter	134 mm
Thickness / Height	30 mm



ILLUMINATOR DATA-ID

BHP1010-X-R-24V

Optical Information						
Part Number	BHP1010-X-R-24V					
LED Color		RED				
Wavelength	(nm)		630			
Intensity (±15%)	(Lux)	17500	15000	12600		
Working Distance	(mm)	10	20	30		
Illumination (number of row)			X			
Illumination Active Area						
Active Length / Outer Diameter	(mm)	102				
Active Width / Inner Diameter	(mm)	104				
Emission angle	(deg.)	0				
Eye Safety Class (IEC62471)	EXEMPT					
Electrical Information						
Lighting Supply Voltage						
(constant voltage mode)		24V ± 2%				
Continuous Current	(mA)		380			
Power Consumption	(W)		9.12			
Lighting casing temperature,						
Operating after 60 minutes	°C		46.3			
Strobe Mode Specification						
Pulse Operation			YES			
Max. Lighting Supply Voltage	(V)	Pulsing at 24	VDC to 48VDC, 0-10% Duty Cycle, Recommer	nded at 36VDC		
(Constant voltage power supply)	(V)	ruisifig at 24	- Duty Cycle, Recommer	idea at 30VDC		
Pulse Current, (Max. 10msec)	(mA)		1140			
(Constant current power supply)	(mA)					
Max. Trigger Pulse Duration	(msec)		10			
Duty Cycle			0-10%			
Additional Information						
Additional Cooling Method		Att	ached to machine part for better heat dissipa	ation		
Intensity Controller Selection			ANG, ST, SD and SDA Series			
CE Conformity			YES			
CE Conformity RoHS Compliance			YES YES			
RoHS Compliance						
ROHS Compliance Connection			YES			
RoHS Compliance Connection Connector Type (default)			YES M12 5 PIN CONNECTOR (MALE)			
RoHS Compliance Connection Connector Type (default) Cable Length (out from lighting)	(mm)		YES M12 5 PIN CONNECTOR (MALE) 700			
RoHS Compliance Connection Connector Type (default)	(mm)	Pin	YES M12 5 PIN CONNECTOR (MALE) 700 Signal	Cable Colour		
RoHS Compliance Connection Connector Type (default) Cable Length (out from lighting)	(mm)	1	YES M12 5 PIN CONNECTOR (MALE) 700 Signal 24V	BROWN		
RoHS Compliance Connection Connector Type (default) Cable Length (out from lighting)	(mm)	1 2	YES M12 5 PIN CONNECTOR (MALE) 700 Signal 24V -	BROWN WHITE		
RoHS Compliance Connection Connector Type (default) Cable Length (out from lighting)	(mm)	1 2 3	M12 5 PIN CONNECTOR (MALE) 700 Signal 24V - GND	BROWN WHITE BLUE		
RoHS Compliance Connection Connector Type (default) Cable Length (out from lighting)	(mm)	1 2 3 4	M12 5 PIN CONNECTOR (MALE) 700 Signal 24V - GND	BROWN WHITE BLUE BLACK		
RoHS Compliance Connection Connector Type (default) Cable Length (out from lighting)	(mm)	1 2 3	M12 5 PIN CONNECTOR (MALE) 700 Signal 24V - GND	BROWN WHITE BLUE		
RoHS Compliance Connection Connector Type (default) Cable Length (out from lighting)	(mm)	1 2 3 4	M12 5 PIN CONNECTOR (MALE) 700 Signal 24V - GND	BROWN WHITE BLUE BLACK		
RoHS Compliance Connection Connector Type (default) Cable Length (out from lighting)	(mm)	1 2 3 4	M12 5 PIN CONNECTOR (MALE) 700 Signal 24V - GND -	BROWN WHITE BLUE BLACK		
ROHS Compliance Connection Connector Type (default) Cable Length (out from lighting) Pin Configuration	(mm)	1 2 3 4	M12 5 PIN CONNECTOR (MALE) 700 Signal 24V - GND M12 5 PIN CONNECTOR (FEMALE)	BROWN WHITE BLUE BLACK		
ROHS Compliance Connection Connector Type (default) Cable Length (out from lighting) Pin Configuration Extension Cable	(mm)	1 2 3 4	M12 5 PIN CONNECTOR (MALE) 700 Signal 24V - GND	BROWN WHITE BLUE BLACK		
Connection Connector Type (default) Cable Length (out from lighting) Pin Configuration Extension Cable Connector Type (default)	(mm)	1 2 3 4	M12 5 PIN CONNECTOR (MALE) 700 Signal 24V - GND M12 5 PIN CONNECTOR (FEMALE)	BROWN WHITE BLUE BLACK		
ROHS Compliance Connection Connector Type (default) Cable Length (out from lighting) Pin Configuration Extension Cable Connector Type (default) Part Number		1 2 3 4	M12 5 PIN CONNECTOR (MALE) 700 Signal 24V - GND GND EXT-FL-M12F-3M-24V	BROWN WHITE BLUE BLACK		
ROHS Compliance Connection Connector Type (default) Cable Length (out from lighting) Pin Configuration Extension Cable Connector Type (default) Part Number Cable Length (out from female connector)		1 2 3 4	M12 5 PIN CONNECTOR (MALE) 700 Signal 24V - GND GND EXT-FL-M12F-3M-24V	BROWN WHITE BLUE BLACK		
Connection Connector Type (default) Cable Length (out from lighting) Pin Configuration Extension Cable Connector Type (default) Part Number Cable Length (out from female connector) Extension Cable		1 2 3 4	M12 5 PIN CONNECTOR (MALE) 700 Signal 24V - GND GND EXT-FL-M12F-3M-24V	BROWN WHITE BLUE BLACK		
Connection Connector Type (default) Cable Length (out from lighting) Pin Configuration Extension Cable Connector Type (default) Part Number Cable Length (out from female connector) Extension Cable (connect to M12 5 Pin Male Connector from		1 2 3 4	M12 5 PIN CONNECTOR (MALE) 700 Signal 24V - GND GND EXT-FL-M12F-3M-24V	BROWN WHITE BLUE BLACK		
Connection Connector Type (default) Cable Length (out from lighting) Pin Configuration Extension Cable Connector Type (default) Part Number Cable Length (out from female connector) Extension Cable (connect to M12 5 Pin Male Connector from		1 2 3 4	M12 5 PIN CONNECTOR (MALE) 700 Signal 24V - GND GND EXT-FL-M12F-3M-24V	BROWN WHITE BLUE BLACK		
Connection Connector Type (default) Cable Length (out from lighting) Pin Configuration Extension Cable Connector Type (default) Part Number Cable Length (out from female connector) Extension Cable (connect to M12 5 Pin Male Connector from		1 2 3 4	M12 5 PIN CONNECTOR (MALE) 700 Signal 24V - GND GND EXT-FL-M12F-3M-24V	BROWN WHITE BLUE BLACK		
Connection Connector Type (default) Cable Length (out from lighting) Pin Configuration Extension Cable Connector Type (default) Part Number Cable Length (out from female connector) Extension Cable (connect to M12 5 Pin Male Connector from		1 2 3 4	M12 5 PIN CONNECTOR (MALE) 700 Signal 24V - GND GND EXT-FL-M12F-3M-24V	BROWN WHITE BLUE BLACK		
Connection Connector Type (default) Cable Length (out from lighting) Pin Configuration Extension Cable Connector Type (default) Part Number Cable Length (out from female connector) Extension Cable (connect to M12 5 Pin Male Connector from		1 2 3 4	M12 5 PIN CONNECTOR (MALE) 700 Signal 24V - GND GND EXT-FL-M12F-3M-24V	BROWN WHITE BLUE BLACK		
Connection Connector Type (default) Cable Length (out from lighting) Pin Configuration Extension Cable Connector Type (default) Part Number Cable Length (out from female connector) Extension Cable (connect to M12 5 Pin Male Connector from		1 2 3 4	M12 5 PIN CONNECTOR (MALE) 700 Signal 24V - GND GND EXT-FL-M12F-3M-24V	BROWN WHITE BLUE BLACK		
Connection Connector Type (default) Cable Length (out from lighting) Pin Configuration Extension Cable Connector Type (default) Part Number Cable Length (out from female connector) Extension Cable (connect to M12 5 Pin Male Connector from		1 2 3 4	M12 5 PIN CONNECTOR (MALE) 700 Signal 24V - GND GND EXT-FL-M12F-3M-24V	BROWN WHITE BLUE BLACK		
Connection Connector Type (default) Cable Length (out from lighting) Pin Configuration Extension Cable Connector Type (default) Part Number Cable Length (out from female connector) Extension Cable (connect to M12 5 Pin Male Connector from lighting)		1 2 3 4	M12 5 PIN CONNECTOR (MALE) 700 Signal 24V - GND GND EXT-FL-M12F-3M-24V	BROWN WHITE BLUE BLACK		
Connection Connector Type (default) Cable Length (out from lighting) Pin Configuration Extension Cable Connector Type (default) Part Number Cable Length (out from female connector) Extension Cable (connect to M12 5 Pin Male Connector from		1 2 3 4	M12 5 PIN CONNECTOR (MALE) 700 Signal 24V - GND GND EXT-FL-M12F-3M-24V	BROWN WHITE BLUE BLACK		
Connection Connector Type (default) Cable Length (out from lighting) Pin Configuration Extension Cable Connector Type (default) Part Number Cable Length (out from female connector) Extension Cable (connect to M12 5 Pin Male Connector from lighting) Application		1 2 3 4	M12 5 PIN CONNECTOR (MALE) 700 Signal 24V - GND EXT-FL-M12F-3M-24V 3000	BROWN WHITE BLUE BLACK		
Connection Connector Type (default) Cable Length (out from lighting) Pin Configuration Extension Cable Connector Type (default) Part Number Cable Length (out from female connector) Extension Cable (connect to M12 5 Pin Male Connector from lighting)		1 2 3 4 5	M12 5 PIN CONNECTOR (MALE) 700 Signal 24V - GND GND EXT-FL-M12F-3M-24V	BROWN WHITE BLUE BLACK GRAY		



Thank you for downloading this document from www.machine-vision-shop.com

If you have any questions, you need help composing the right package for your application or do you want to order?

Feel free to contact us via e-mail at sales@vision-consultancy.nl or visit our webshop.

Our vision experts are happy to help you.



Natascha Overhof



Christian Crompvoets



VISION CONSULTANCY

Robert Schumandomein 2 6229 ES Maastricht The Netherlands

+31 (0) 438 522 651

sales@vision-consultancy.nl www.machine-vision-shop.com

