

LBRX-00-040-6-R-24V

Lighting Dimension 40 31.5 26.3 31.50 Q 22 15.50 0 6.50 0 0 ADJUSTABLE RANGE 34.6 2X TAP M3 $\sqrt{4}$ (ON 2 SIDES) 2X M3 ADJUSTABLE NUT q (0) CABLE & CONNECTOR ROHS CE

Mechanical Information				
Casing Material	Aluminium			
Storage Temperature Range	Temp 0 - 45°C, Humidity 20-85%			
Weight	70 g			
Length / Outer Diameter	52 mm			
Width / Inner Diameter	31.5 mm			
Thickness / Height	22 mm			



LBRX-00-040-6-R-24V

Optical Information							
Part Number		LBRX-00-040-6-R-24V					
LED Color			RED				
Wavelength	(nm)						
		630 5820 3700 2930					
Intensity (±15%)	(Lux)						
Working Distance	(mm)	100	130	150			
Illumination (number of row)			6				
Illumination Active Area							
Active Length / Outer Diameter	(mm)		40				
Active Width / Inner Diameter	(mm)	26.3					
Emission angle	(deg.)	0					
Eye Safety Class (IEC62471)	EXEMPT						
Electrical Information							
Lighting Supply Voltage							
(constant voltage mode)			24V ± 2%				
Continuous Current	(mA)		78				
Power Consumption	(W)		1.87				
Lighting casing temperature,	(***)	1.0/					
Operating after 60 minutes	°C	49.6					
Operating after 60 minutes		·C 49.6					
Strobe Mode Specification							
Pulse Operation		YES					
Max. Lighting Supply Voltage	0.0						
(Constant voltage power supply)	(V)	Pulsing at 24VDC to 48VDC, 0-10% Duty Cycle, Recommended at 36VDC					
Pulse Current, (Max. 10msec)							
(Constant current power supply)	(mA)		234				
Max. Trigger Pulse Duration	(msec)		10				
Duty Cycle	(msec)	10 0-10%					
Suty Cyclic			0 10/0				
Additional Information							
Additional information							
Additional Cooling Method		Attached to machine part for better heat dissipation					
Intensity Controller Selection		ANG, ST, SD and SDA Series					
CE Conformity		YES					
RoHS Compliance		YES					
,			-				
Connection							
Connector Type (Default):		JST SMR-03V					
Cable Length out from lighting :	(mm)	500					
Pin Configuration :	()	Pin	Signal	Cable Color			
Till Colligaration .		1	LED +	RED			
	—	2		VED			
	 		N.C.				
	 	3	LED -	WHITE			
			_				
Application							
Illumination Type		Direct Illumination					
manimation type		General illumination, label inspection, character inspection, code recognition.					
Applicattion Use		Conoral illumination	label inspection, character inspection, sed	agnition			



Thank you for downloading this document from www.machine-vision-shop.com

If you have any questions, you need help composing the right package for your application or do you want to order?

Feel free to contact us via e-mail at sales@vision-consultancy.nl or visit our webshop.

Our vision experts are happy to help you.



Natascha Overhof



Christian Crompvoets



VISION CONSULTANCY

Robert Schumandomein 2 6229 ES Maastricht The Netherlands

+31 (0) 438 522 651

sales@vision-consultancy.nl www.machine-vision-shop.com

