


## LBL3-00-500-3-G-24V

## **Lighting Dimension**







Mechanical Information	
Casing Material	Aluminium
Storage Temperature Range	Temp 0-45°C, Humidity 20-85%
Weight	530 g
Length / Outer Diameter	520 mm
Width / Inner Diameter	26.3 mm
Thickness / Height	32.8 mm



## LBL3-00-500-3-G-24V

LBL3-00-500-3-G-24V  GREEN  525  20 3  499  19.7 0 EXEMPT  24V ± 2% 750 18	30
GREEN 525  20 3  499 19.7 0 EXEMPT  24V ± 2% 750 18	
20 3 3 499 119.7 0 EXEMPT  24V ± 2% 750 18	
20 3 499 19.7 0 EXEMPT 24V ± 2% 750 18	
3 499 19.7 0 EXEMPT  24V ± 2% 750 18	
3 499 19.7 0 EXEMPT  24V ± 2% 750 18	
499 19.7 0 EXEMPT 24V ± 2% 750 18	
19.7 0 EXEMPT  24V ± 2%  750  18	
19.7 0 EXEMPT  24V ± 2%  750  18	
0 EXEMPT  24V±2%  750  18	
24V ± 2% 750 18	
750 18	
750 18	
750 18	
750 18	
18 YES	
YES	
ing at 24VDC to 48VDC, 0-10% Duty Cycle. Recommende	
	24 24 36VDC
5,, -,,	ed at 36VDC
2250	
2250	
10	
0-10%	
Attached to machine part for better heat dissipation	on
ANG, SD, ST & SDA Series	-
YES	
YES	
JST SMR-03V	
500	
Signal	Cable Color
LED +	RED
N.C.	
LED -	WHITE
	WITHE
14.	
Direct Illumination	



Thank you for downloading this document from www.machine-vision-shop.com

If you have any questions, you need help composing the right package for your application or do you want to order?

Feel free to contact us via e-mail at sales@vision-consultancy.nl or visit our webshop.

Our vision experts are happy to help you.



Natascha Overhof



Christian Crompvoets



## **VISION** CONSULTANCY

Robert Schumandomein 2 6229 ES Maastricht The Netherlands

+31 (0) 438 522 651

sales@vision-consultancy.nl www.machine-vision-shop.com

