

## LBM-00-080-2-B-24V

## EMITTING AREA 9.10 7.10 TAP M2X0.4 - \$\tilde{\pi}\$ 4.10 TAP M2X0.4 - \$\tilde{\pi}\$ 4.10 TAP M2X0.4 - \$\tilde{\pi}\$ 3.10 NOT THRU SOCM CABLE NOT THRU



(BOTH SIDES)

Mechanical Information	
Casing Material	Aluminium
Storage Temperature Range	Temp 0-45°C, Humidity 20-85%
Weight	27 g
Length / Outer Diameter	92 mm
Width / Inner Diameter	13 mm
Thickness / Height	9.1 mm

## LBM-00-080-2-B-24V

Optical Information							
Part Number	1	LBM-00-080-2-B-24V					
LED Color			BLUE				
Wavelength	(nm)		470				
Intensity (±15)	(Lux)	TBA					
Working Distance	(mm)	10	20	30			
Illumination (number of row)			2				
Illumination Active Area							
Active Length / Outer Dia.	(mm)	84.4					
Active Width / Inner Dia.	(mm)		9.6				
Emission angle	(deg.)	0					
Eye Safety Class ( IEC62471 )		ll ll					
*CHROMATICITY TABLE							
Electrical Information							
Lighting Supply Voltage							
(constant voltage mode)		24V ± 2%					
Continuous Current	(mA)	104					
Power Consumption	(W)	2.496					
Lighting casing temperature,		••					
Operating after 60 minutes	°C	49.4					
Strobe Mode Specification							
Pulse Operation		YES					
Max. Lighting Supply Voltage		Pulsing at 24VDC to 48VDC, 0-10% Duty Cycle					
(Constant voltage power supply)	(V)	Recommended at 36VDC					
Pulse Current, (Max. 10msec)							
(Constant current power supply)	(mA)	312					
Max. Trigger Pulse Duration	(msec)	10					
Duty Cycle	(msee)	0-10%					
Additional Information							
Additional Cooling Method		Attached to machine part for better heat dissipation					
Intensity Controller Selection		ANG, SD, ST & SDA series					
CE Conformity		YES					
RoHS Compliance		YES					
	'						
Connection							
Connector Type (Default):		JST SMR-03V					
Cable Length out from lighting :	(mm)	500					
Pin Configuration :		Pin	Signal	Cable Color			
		1	LED +	RED			
		2	N.C.				
		3	LED -	WHITE			
Application							
Illumination Type		Direct Illumination					
Application Use		General illumination, label inspection, character inspection, code recognition					



Thank you for downloading this document from www.machine-vision-shop.com

If you have any questions, you need help composing the right package for your application or do you want to order?

Feel free to contact us via e-mail at sales@vision-consultancy.nl or visit our webshop.

Our vision experts are happy to help you.



Natascha Overhof



Christian Crompvoets



## **VISION** CONSULTANCY

Robert Schumandomein 2 6229 ES Maastricht The Netherlands

+31 (0) 438 522 651

sales@vision-consultancy.nl www.machine-vision-shop.com

