


LBRQ-00-160-6-R-24V

Lighting Dimension



Mechanical Information	
Casing Material	Aluminium
Storage Temperature Range	Temp 0 - 45°C, Humidity 20-85%
Weight	800 g
Length / Outer Diameter	240 mm
Width / Inner Diameter	190 mm
Thickness / Height	34.2 mm



LBRQ-00-160-6-R-24V

Optical Information						
Part Number	LBRQ-00-160-6-R-24V					
LED Color			RED			
Wavelength	(nm)		630			
Intensity (±15%)	(Lux)	TBA	TBA	TBA		
Working Distance	(mm)	302	313	323		
Illumination (number of row)	` `		6			
Illumination Active Area						
Active Length / Outer Diameter	(mm)		240			
Active Width / Inner Diameter	(mm)	190				
Emission angle	(deg.)		0			
Eye Safety Class (IEC62471)			EXEMPT			
Electrical Information						
Lighting Supply Voltage						
(constant voltage mode)		24V ± 2%				
Continuous Current	(mA)	1152				
Power Consumption	(W)	27.65				
Lighting casing temperature,						
Operating after 60 minutes	°C	°C TBA				
Strobe Mode Specification						
Pulse Operation		YES				
Max. Lighting Supply Voltage						
(Constant voltage power supply)	(V)	Pulsing at 24VDC to 48VDC, 0-10% Duty Cycle, Recommended at 36VDC				
Pulse Current, (Max. 10msec)						
(Constant current power supply)	(mA)	3456				
Max. Trigger Pulse Duration	(msec)	c) 10				
Duty Cycle	(IIIsec)	0-10%				
Additional Information						
Additional Cooling Method		Attached to machine part for better heat dissipation				
Intensity Controller Selection		ANG, ST, SD and SDA Series				
CE Conformity	YES					
RoHS Compliance	YES					
Connection						
Connector Type (Default):		JST SMR-03V				
Cable Length out from lighting :	(mm)		500			
Pin Configuration :		Pin	Signal	Cable Color		
		1	LED +	RED		
		2	N.C.			
		3	LED -	WHITE		
Application	Direct Illumination					
Illumination Type Applicattion Use						
Application USE	General illumination, label inspection, character inspection, code recognition.					



Thank you for downloading this document from www.machine-vision-shop.com

If you have any questions, you need help composing the right package for your application or do you want to order?

Feel free to contact us via e-mail at sales@vision-consultancy.nl or visit our webshop.

Our vision experts are happy to help you.



Natascha Overhof



Christian Crompvoets



VISION CONSULTANCY

Robert Schumandomein 2 6229 ES Maastricht The Netherlands

+31 (0) 438 522 651

sales@vision-consultancy.nl www.machine-vision-shop.com

