

LBRX-00-040-6-G-24V

Lighting Dimension 40 31.5 26.3 31.50 Q 22 15.50 0 6.50 0 0 ADJUSTABLE RANGE 34.6 2X TAP M3 $\sqrt{4}$ (ON 2 SIDES) 2X M3 ADJUSTABLE NUT q (0) CABLE & CONNECTOR ROHS CE

Mechanical Information			
Casing Material	Aluminium		
Storage Temperature Range	Temp 0 - 45°C, Humidity 20-85%		
Weight	70 g		
Length / Outer Diameter	52 mm		
Width / Inner Diameter	31.5 mm		
Thickness / Height	22 mm		



LBRX-00-040-6-G-24V

Optical Information						
Part Number			LBRX-00-040-6-G-24V			
LED Color			GREEN			
Wavelength	(nm)	525				
Intensity (±15%)	(Lux)	6960 4430 3450				
Working Distance	(mm)	100	130	150		
Illumination (number of row)	(,		6			
Illumination Active Area						
Active Length / Outer Diameter	(mm)	40				
Active Width / Inner Diameter	(mm)		26.3			
Emission angle	(deg.)	0				
Eye Safety Class (IEC62471)	(deg.)	EXEMPT				
Eye Surety class (1ECO2471)			EALWI T			
Electrical Information						
Lighting Supply Voltage			·			
(constant voltage mode)		24V ± 2%				
Continuous Current	(mA)	72				
Power Consumption	(W)		1.73			
Lighting casing temperature,	(**)	1./3				
Operating after 60 minutes	°C		47.3			
Strobe Mode Specification			1177			
Pulse Operation			YES			
Max. Lighting Supply Voltage	(V)	Pulsing at 24VDC to 48VDC, 0-10% Duty Cycle, Recommended at 36VDC				
(Constant voltage power supply)	(*)	ruising at 24	VDC to 48VDC, 0-10% Daty Cycle, Necolimena	ed at 30VDC		
Pulse Current, (Max. 10msec)	(.)					
(Constant current power supply)	(mA)	216				
Max. Trigger Pulse Duration	(msec)		10			
Duty Cycle	(msee)	0-10%				
Additional Information						
Additional information						
Additional Cooling Method		Attached to machine part for better heat dissipation				
Intensity Controller Selection			ANG, ST, SD and SDA Series			
CE Conformity		YES				
RoHS Compliance		YES				
Connection						
Connector Type (Default):	, .	JST SMR-03V				
Cable Length out from lighting :	(mm)		500			
Pin Configuration :		Pin	Signal	Cable Color		
		1	LED +	RED		
		2	N.C.			
		3	LED -	WHITE		
Application						
Illumination Tune		Direct Illumination				
Illumination Type Applicattion Use		Direct Illumination				
IApplicattion Lice		General illumination, label inspection, character inspection, code recognition.				



Thank you for downloading this document from www.machine-vision-shop.com

If you have any questions, you need help composing the right package for your application or do you want to order?

Feel free to contact us via e-mail at sales@vision-consultancy.nl or visit our webshop.

Our vision experts are happy to help you.



Natascha Overhof



Christian Crompvoets



VISION CONSULTANCY

Robert Schumandomein 2 6229 ES Maastricht The Netherlands

+31 (0) 438 522 651

sales@vision-consultancy.nl www.machine-vision-shop.com

