
ILLUMINATOR DATA-ID

LSW-00-040-2-B-24V

TMS



| Mechanical Information | |
|---------------------------|--------------------------------|
| Casing Material | Aluminium |
| Storage Temperature Range | Temp 0 - 45°C, Humidity 20-85% |
| Weight | 40 g |
| Length / Outer Diameter | 43 mm |
| Width / Inner Diameter | 15 mm |
| Thickness / Height | 20 mm |

ILLUMINATOR DATA-ID

LSW-00-040-2-B-24V

TINS

| Optical Information | | | | | | |
|----------------------------------|--------|---|--|-------------|--|--|
| Part Number | | | LSW-00-040-2-B-24V | | | |
| LED Color | | BLUE | | | | |
| Wavelength | (nm) | 470 | | | | |
| Intensity (±15%) | (Lux) | 19500 | 18000 | 16800 | | |
| Working Distance | (mm) | 65 | 70 | 75 | | |
| Illumination (number of row) | | | 2 | | | |
| Illumination Active Area | | | | | | |
| Active Length / Outer Diameter | (mm) | 36 | | | | |
| Active Width / Inner Diameter | (mm) | 16 | | | | |
| Emission angle | (deg.) | 0 | | | | |
| Eye Safety Class (IEC62471) | | EXEMPT | | | | |
| Electrical Information | | | | | | |
| Lighting Supply Voltage | | | | | | |
| (constant voltage mode) | | 24V ± 2% | | | | |
| Continuous Current | (mA) | 75 | | | | |
| Power Consumption | (W) | 1.8 | | | | |
| Lighting casing temperature, | | | | | | |
| Operating after 60 minutes | Ů | °C 58 | | | | |
| Strobe Mode Specification | | | | | | |
| Pulse Operation | | YES | | | | |
| Max. Lighting Supply Voltage | | 165 | | | | |
| (Constant voltage power supply) | (∨) | Pulsing at 24 | VDC to 48VDC, 0-10% Duty Cycle, Recommende | d at 36VDC | | |
| | | | | | | |
| Pulse Current, (Max. 10msec) | (mA) | 225 | | | | |
| (Constant current power supply) | (| 10 | | | | |
| Max. Trigger Pulse Duration | (msec) | (msec) 10 0-10% | | | | |
| Duty Cycle | | | 0-10% | | | |
| Additional Information | | | | | | |
| Additional Cooling Method | | Attached to machine part for better heat dissipation | | | | |
| Intensity Controller Selection | | Attached to indefine part for better heat dissipation | | | | |
| CE Conformity | | YES | | | | |
| RoHS Compliance | | YES | | | | |
| | | | 125 | | | |
| Connection | | | | | | |
| Connector Type (Default): | | JST SMR-03V | | | | |
| Cable Length out from lighting : | (mm) | | 500 | | | |
| Pin Configuration : | | Pin | Signal | Cable Color | | |
| | | 1 | LED + | RED | | |
| | | 2 | N.C. | | | |
| | | 3 | LED - | WHITE | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| Application | | | | | | |
| Illumination Type | | Direct Illumination | | | | |
| Applicattion Use | | Substrate inspection, label inspection, flat surface, fiducially recognition. | | | | |



Thank you for downloading this document from www.machine-vision-shop.com

If you have any questions, you need help composing the right package for your application or do you want to order?

Feel free to contact us via e-mail at sales@visionconsultancy.nl or visit our webshop.

Our vision experts are happy to help you.



Natascha Overhof



Christian Crompvoets



VISION CONSULTANCY

Robert Schumandomein 2 6229 ES Maastricht The Netherlands

+31 (0) 438 522 651

sales@vision-consultancy.nl www.machine-vision-shop.com Scan me to visit machine-vision-shop

